




A *tensar* Company

MATERIAL SPECIFICATION

P550



The composite turf reinforcement mat (C-TRM) shall be a machine-produced mat of 100% UV stabilized polypropylene fibre matrix incorporated into a permanent three-dimensional turf reinforcement matting.

The matrix shall be evenly distributed across the entire width of the matting and stitch bonded between the bottom and middle ultra heavy duty UV stabilized nettings with 1.27 x 1.27 cm openings and then covered by an ultra heavy duty UV stabilized nettings with 1.27 x 1.27 cm openings. The middle, dramatically corrugated (crimped) netting shall form prominent closely spaced ridges across the entire width of the mat. The three nettings shall be stitched together on 3.81 cm centers with UV stabilized polypropylene thread to form a permanent three-dimensional turf reinforcement matting.

The P550 shall meet requirements established by the Erosion Control Technology Council (ECTC) Specification and the U.S. Department of Transportation, Federal Highway Administration's (FHWA) *Standard Specifications For Construction of Roads and Bridges on Federal Highway Projects, FP-03 2003 Section 713.18* as a *Type 5A, B, and C Permanent Turf Reinforcement Mat*.

Installation staple patterns shall be clearly marked on the turf reinforcement mattings with environmentally safe paint. All mats shall be manufactured with a colored thread stitched along both outer edges 5-12.5 cm from the edge as an overlap guide for adjacent mats.

The composite turf reinforcement mat shall be the North American Green P550, or equivalent. The P550 permanent composite turf reinforcement mat shall have the following physical properties:

Material Content

Matrix	100% UV Stabilized Polypropylene Fibre 0.27 kg/m ²
Netting	Top and bottom- Ultra Heavy Duty UV Stabilized Polypropylene 11.7 kg/100 m ² Mid – Corrugated Ultra Heavy Duty UV Stabilized Polypropylene 11.7 kg/100 m ²
Thread	UV Stabilized Polypropylene

P550 is Available with the Following Physical Specifications Per Roll

Width	2.00 m
Length	16.90 m
Weight ± 10%	23.59 kg
Area	33.80 m ²

Stitch Spacing for All Rolls = 3.81 cm